



Europäisches Patentamt
European Patent Office
Office européen des brevets



EP 0 951 898 A1

EUROPEAN PATENT APPLICATION

(12)

(43) Date of publication:
27.10.1999 Bulletin 1999/43

(51) Int Cl.⁶: **A61K 7/06, A61K 7/50**

(21) Application number: 99300932.3

(22) Date of filing: 09.02.1999

(84) Designated Contracting States:
AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE
Designated Extension States:
AL LT LV MK RO SI

(30) Priority: 10.02.1998 US 74249 P
04.02.1999 US 245138

(71) Applicant: **Johnson & Johnson Consumer Companies, Inc.**
Skillman, New Jersey 08558-9418 (US)


(72) Inventors:

- **Li, Jun**
Shangai, China 200041 (CN)
- **Parr, Deborah J.**
Belle Mead, NJ 08502 (US)

**(74) Representative: Mercer, Christopher Paul
Carpmaels & Ransford
43, Bloomsbury Square
London WC1A 2RA (GB)**

(54) Hair conditioning compositions

(57) The present invention relates to hair conditioning or detangling compositions comprising from about 0.01 percent to about 2.0 percent by weight of a quaternary ammonium compound of the formula:



and from about 0.01 percent to about 2.0 percent by weight of a silicone compound, wherein R is a substituted or unsubstituted alkyl or alkenyl group having from about 11 to about 35 carbon atoms, X is - O - or N-R₅, R₁ is a substituted or unsubstituted alkylene group having from about 2 to about 6 carbon atoms, R₂, R₃ and R₄ are each independently an alkyl or hydroxyalkyl group having from about 1 to about 4 carbon atoms, R₅ is H or CH₃, and A₁ is chloride; bromide; alkylsulfate containing from about one to about two carbon atoms; or mixtures thereof.

EP 0 951 898 A1

Description

Field of the Invention

- 5 [0001] The present invention relates to compositions that are useful in conditioning hair, especially in the form of a leave-on hair conditioner or hair detangler.

Background

- 10 [0002] Compositions that can be used to condition hair are well known. Hair conditioning compositions are intended to leave the hair manageable, soft, and shiny. Manageability is manifested as ease of combing in the wet and dry states, as well as preventing hair "fly-away" in the dry state. Most hair conditioning compositions are applied to the hair when wet, usually as an after-treatment following shampooing. More recently, two-in-one conditioning shampoos have been developed which provide cleansing and conditioning of the hair with a single composition. Both the after-treatment conditioners and the two-in-one shampoos are usually rinsed off after being allowed to remain in contact with the hair for a brief period of time, and hence, are referred to in the art as "rinse-off" type compositions. While the hair conditioning compositions of the present invention may be used in rinse-off products, they are particularly directed to a "leave-on" product, i.e., one which is applied to the hair in either a wet or dry state, and is not subsequently rinsed off. Such leave-on products are typically applied to the hair from a pump-type spray dispenser in a form ranging from a mist to a liquid stream.
- 20 [0003] U.S. 4,374,825 discloses hair conditioning compositions comprising from about 1 to about 13% of a volatile liquid hair conditioning agent selected from hydrocarbons and silicones, from 0.1 to about 8% of a water soluble nonionic polymer thickening agent and from about 0.05 to about 4% of a cationic agent selected from quaternary ammonium salts or salts of fatty amines. The compositions of the '825 patent are in the form of emulsions.
- 25 [0004] U.S. 4,387,090 discloses hair conditioning compositions comprising from 1 to 99% volatile hydrocarbon or silicone and up to about 1% of a hydrophobic polymeric thickening agent. The composition optionally comprises up to about 4% of a cationic conditioning agent selected from quaternary ammonium salts and salts of fatty amines.
- [0005] U.S. 4,711,776 discloses hair cosmetic compositions comprising 0.01 to about 20% branched quaternary ammonium salts and 0.1 to 30% oils and fats selected from higher alcohols and fatty acid monoglycerides.
- 30 [0006] U.S. 4,777,037 discloses hair conditioning compositions comprising 1 to 4% polydimethyl cyclosiloxane and 0.5 to 5% of a quaternary nitrogen-containing conditioning agent having two long chain alkyl groups, each of said alkyl groups having from 12 to 18 carbon atoms. Preferred compositions are said to further comprise 0.5 to 10% fatty alcohol and 0.1 to 2% of a tertiary amidoamine. The compositions of this patent are in the form of emulsions.
- 35 [0007] U.S. 4,784,844 discloses silicone emulsions comprising 100 parts by weight cyclic siloxane; from 0.7 to 666 parts emulsifier selected from ethoxylated fatty acids, ethoxylated and non-ethoxylated sorbitan esters, ethoxylated alkyl phenols and ethoxylated ethers; and from 5 to 960 parts water, all parts being in parts by weight. The emulsions are said to be useful for cosmetic and medicinal purposes.
- [0008] U.S. 4,859,457 discloses hair rinse compositions comprising 0.05 to 0.5% of a cationic surface active agent and a second component selected from higher alcohols and monoglycerides, said second component being present in the composition at 3 to 15 times the weight of the cationic surface active agent.
- 40 [0009] U.S. 4,982,728 is directed to pumpable cationic fatty alcohol dispersions said to have application in cosmetic hair care and skin care preparations. The dispersions comprise from 10 to 25% by weight of a fatty alcohol and from 0.01 to 1% by weight of a cationic surface active compound.
- [0010] U.S. 4,902,499 discloses hair conditioner compositions comprising from 0.01 to 10% of a rigid silicone polymer and a volatile carrier. In some embodiments, the compositions additionally comprise from 0.1 to 10% of a lipid vehicle material (preferably selected from fatty alcohols, fatty esters and monoglycerides) and from 0.05 to 5% of a cationic surfactant (preferably a di-fatty alkyl quaternary ammonium compound).
- 45 [0011] U.S. 4,910,013 discloses hairdressing compositions comprising branched alkyl quaternary ammonium compounds and silicone compounds.
- 50 [0012] U.S. 4,950,468 discloses a hair treating composition comprising from 0.05 to 2.5% of a dimethyl silicone rubber and from 0.1 to 5.0% of a mixture of stearyl trimonium chloride and behenyl trimonium chloride. The components of the composition are said to adsorb strongly to hair and they are not readily desorbed, even by washing.
- [0013] U.S. 4,954,335 discloses a hair conditioning composition comprising from 0.1 to 5% of a quaternary ammonium compound (preferably containing two fatty alkyl groups), from 0.1 to 5% of an amidoamine, from 0.5 to 5% of a volatile conditioning compound selected from silicone and aliphatic hydrocarbon, from 1 to 10% of a non-ionic surfactant, preferably, a fatty alkyl pyrrolidone, and from 10 to 30% of a polyhydric alcohol, all in a suitable liquid vehicle.
- 55 [0014] U.S. 4,973,476 discloses leave-on hair conditioning compositions comprising 75 to 99.9% volatile silicone and from 0.1 to 10% of at least one functional silicone. The compositions may further comprise optional ingredients

such as anti-static agents, organic esters and surfactants, among others.

[0015] U.S. 4,976,956 discloses hair-treating compositions comprising at least 0.35% of a water-soluble quaternary ammonium compound, from 0.4 to 15% of an oil soluble, water-dispersible quaternary ammonium compound, from 0.1 to 5% of an acid-neutralized amidoamine, from 0.1 to 2% of a polydimethylsiloxane and a suitable liquid vehicle.

The compositions may further contain optional ingredients such as organic co-solvents, illustrative members including lower alcohols, glycols and polyols. Other optional ingredients include long chain fatty alcohols. The compositions are said to be useful either in leave-on or in rinse off products.

[0016] U.S. 5,002,762 discloses hair conditioning compositions comprising 0.5 to 12% of particular volatile silicone compounds, 0.5 to 3% of a lipid vehicle material such as fatty alcohols or fatty esters, and 0.2 to 4% of a cationic surfactant.

[0017] U.S. 5,288,484 discloses a pre-shampoo conditioning composition comprising from 0.1 to 20% of a particular cationic cellulose, from 0.05 to 20% of a poly (allyldimethylammonium) polymer and from 0.2 to 10% of behenamido-propyl dihydroxypropyl dimonium chloride.

[0018] U.S. 5,290,555 discloses a hair conditioner comprising an oil phase and an aqueous phase. The oil phase comprises a variety of volatile and non-volatile silicone components. The aqueous phase comprises olealkonium chloride and PEG-8.

[0019] U.S. 5,374,421 discloses hair treatment compositions comprising 0.1 to 10% of a silicone polymer having at least one alkoxy group containing 12 to 22 carbon atoms, said polymer having a melting point of not less than 30°C; 0.1 to 20% of a cationic surface active agent; 0.1 to 30% of an alcohol having from 12 to 26 carbon atoms; 0.1 to 90% of a water-compatible organic alcohol; and water.

[0020] WO 97/07774 discloses a hair treatment composition particularly useful as a rinse-off product that comprises 0.6 to about 10% of a fatty alcohol, 0.01 to 15% of a silicone conditioning agent and from 0.1 to 5% of a monoalkyl trimethylammonium salt. The silicone conditioning agent is preferably non-volatile, and the ammonium salt is preferably behenyl trimethylammonium chloride.

[0021] While a number of the above references disclose the combination of silicones and quaternary ammonium salts, we are unaware of any references that disclose hair care compositions that incorporate a silicone compound in conjunction with a fatty quaternary ammonium compound wherein the fatty group is an acyl group, derived, for example, from an amide or ester.

[0022] There are a number of important requirements for a leave-on conditioner composition. First, the composition must impart the desired conditioning benefits of manageability, softness and shine. Second, the product should be physically and chemically stable. Third, the composition should be mild and non-irritating to the skin and eyes. This property is especially important when the composition is used on children. Fourth, the product should leave minimal residue on the hair. Finally, the composition should have physical properties such as viscosity that permit its application from a spray dispenser.

[0023] Accordingly, one object of the present invention is a conditioning composition that delivers the requisite benefits of hair manageability, softness and shine.

[0024] Another object of the invention is to provide a composition that delivers the requisite conditioning benefits and is both physically and chemically stable.

[0025] Another object of the invention is to provide a composition that delivers the requisite conditioning benefits and is mild and non-irritating to the skin and eyes.


[0026] Another object of the invention is to provide a composition that delivers the requisite conditioning benefits and can be applied to and left on the hair without leaving appreciable residue on the hair.

[0027] Another object of the invention is to provide a composition that delivers the requisite conditioning benefits and can be applied to the hair in a variety of physical forms, including a spray.

Summary of the Invention

[0028] The present invention relates to a hair conditioning composition which comprises, based upon the total weight of the composition:

A. about 0.01 percent to about 2.0 percent of a quaternary ammonium compound of the formula



and


B. about 0.01 percent to about 2.0 percent of a silicone compound

wherein


R is a substituted or unsubstituted alkyl or alkenyl group having from about 11 to about 35 carbon atoms,
 X is - O - or N-R₅,
 R₁ is a substituted or unsubstituted alkylene group having from about 2 to about 6 carbon atoms,
 R₂, R₃ and R₄ are each independently an alkyl or hydroxyalkyl group having from about 1 to about 4 carbon atoms,
 R₅ is H or CH₃, and
 A₁ is chloride; bromide; alkylsulfate containing from about one to about two carbon atoms; or mixtures thereof.

[0029] In a preferred embodiment, the invention relates to a conditioning composition comprising:

A. a first quaternary ammonium compound of the formula



B. a second quaternary ammonium compound of the formula



and

C. based upon the total weight of the composition, from about 0.01 percent to about 2.0 percent of a silicone compound


wherein

R is a substituted or unsubstituted alkyl or alkenyl group having from about 11 to about 35 carbon atoms,
 X is - O - or N-R₅,
 R₁ is a substituted or unsubstituted alkylene group having from about 2 to about 6 carbon atoms,
 R₂, R₃ and R₄ are each independently an alkyl or hydroxyalkyl group having from about 1 to about 4 carbon atoms,
 R₅ is H or CH₃,
 R₆ is an alkyl or alkenyl group having from about 12 to about 36 carbon atoms,
 R₇ is an alkyl or alkenyl group having from about one to about 36 carbon atoms or a benzyl group,
 R₈ and R₉ are each independently an alkyl group having from about 1 to about 4 carbon atoms or a benzyl group,
 A₁ and A₂ are each independently chloride; bromide; alkylsulfate containing from about one to about two carbon atoms; or mixtures thereof,


and wherein said first and said second quaternary ammonium compounds together comprise between about 0.01 percent to about 2.0 percent by weight of said composition.

[0030] Another preferred embodiment of the invention relates to a hair conditioning composition comprising:

A. a first quaternary ammonium compound of the formula



B. a second quaternary ammonium compound of the formula



and

C. based upon the total weight of the composition, from about 0.01 to about 2.0 percent by weight of a volatile silicone compound

wherein

R is an alkyl or alkenyl group having from about 17 to about 21 carbon atoms,

X is -O- or N-H,

R₁ is a substituted or unsubstituted alkylene group having from about 2 to about 6 carbon atoms,

R₂, R₃ and R₄ are each independently an alkyl or hydroxyalkyl group having from about 1 to about 4 carbon atoms,

R₆ is an alkyl or alkenyl group having from about 18 to about 22 carbon atoms,


R₇, R₈ and R₉ are each independently an alkyl group having from about 1 to about 4 carbon atoms or a benzyl group,

A₁ and A₂ are each independently chloride; bromide; alkylsulfate containing from about one to about two carbon atoms; or mixtures thereof,


and wherein said first and said second quaternary ammonium compounds together comprise between about 0.01 to about 2.0 percent by weight of said composition.

[0031] Another embodiment of the invention relates to a conditioning composition comprising, based upon the total weight of the composition:

A. from about 0.05 percent to about 1.0 percent of a first quaternary ammonium compound of the formula



B. from about 0.05 percent to about 1.0 percent of a second quaternary ammonium compound of the formula



and

C. from about 0.05 to about 1.0 percent of a volatile silicone compound having from about 4 to about 6 silicon atoms,

wherein

R is an alkyl group having about 21 carbon atoms,

X is N-H,

R₁ is a substituted or unsubstituted alkylene group having from about 2 to about 6 carbon atoms,

R₂, R₃ and R₄ are each independently an alkyl or hydroxyalkyl group having from about 1 to about 4 carbon atoms,


R₅ is an alkyl group having about 22 carbon atoms,

R₇, R₈ and R₉ are each independently CH₃,

A₁ and A₂ are each independently chloride; bromide; alkylsulfate containing from about one to about two carbon atoms; or mixtures thereof.

Detailed Description of the Invention

[0032] In a first embodiment, the invention relates to hair conditioning compositions comprising a quaternary ammonium compound of the formula



wherein

R is a substituted or unsubstituted alkyl or alkenyl group having from about 11 to about 35 carbon atoms;

X is -O- or N-R₅;

R₁ is an alkylene group having from about 2 to about 6 carbon atoms, said alkylene group being unsubstituted or substituted, e.g., with a functional group such as a hydroxyl group;


R₂, R₃ and R₄ are each independently an alkyl or hydroxyalkyl group having from about 1 to about 4 carbon atoms. Illustrative hydroxyalkyl groups being hydroxyethyl, hydroxypropyl or dihydroxypropyl;

R₅ is H or CH₃; and




A₁ is chloride; bromide; alkylsulfate containing from about one to about two carbon atoms; or mixtures thereof.

[0033] It is well known in the art that long chain functional hydrocarbons are materials that occur in nature as mixtures of varying chain length. Accordingly, in the case of refined materials, R may represent a group having a single chain length. Alternatively, in the case of less refined materials, R may represent a material having a mixture of different chain lengths within the broadest prescribed range.

[0034] In a preferred embodiment, the quaternary ammonium compound I has the structure shown hereinabove wherein R is an alkyl group having from about 17 to about 21 carbon atoms, preferably from about 19 carbon atoms to about 21 carbon atoms, and more preferably about 21 carbon atoms, or mixtures thereof; X is an N-R₅ group; R₅ is H and the other structural elements are as hereinabove defined. The composition of the invention comprises, based upon the total weight of the composition, from about 0.01 percent to about 2.0 percent, preferably from about 0.05 percent to about 1.0 percent, and more preferably from about 0.1 to about 0.5 percent by weight of the quaternary ammonium compound. Exemplary materials useful as the quaternary ammonium compound in the compositions of the invention include compounds having the formula II through V below:



II




[0035] The compound of formula II wherein A_1 is ethosulfate is available as "Schercoquat BAS" from Scher Chemicals, Inc. of Clifton, New Jersey. The compound of formula III wherein A_1 is chloride is available as "Lexquat AMG-BEO" from Inolex Chemical Co. of Philadelphia, PA. The compound of formula IV wherein A_1 is chloride is available as "Akypoquat 131" from Chemische Fabrik Chem-Y of Emmerich, Germany. The compound of formula V wherein A_1 is chloride is available as "Incroquat Behenyl HE" from Croda, Inc. of Parsippany, New Jersey. The latter material, which is a 50% mixture of the compound of formula V in hexylene glycol, is a preferred source of the quaternary ammonium compound useful in the compositions of the invention.

[0036] The compositions of the invention further comprise, based upon the total weight of the composition, from about 0.01 percent to about 2.0 percent, and preferably from about 0.05 percent to about 1.0 percent of an organic silicone compound. Preferably, suitable silicone compounds are in the form of a fluid or a gum. Silicone compounds useful in the compositions of the invention include, but are not limited to dimethicones, which are a mixture of fully methylated linear siloxane polymers end blocked with trimethylsiloxy units; cyclomethicones, which are cyclic dimethyl polysiloxane compounds having from about 3 to about 6 silicon atoms; and mixtures thereof.

[0037] The organic silicone compounds useful in the compositions of the invention are preferably volatile, i.e., they have a boiling point below about 250°C . The cyclomethicones having between about 4 and about 6 silicon atoms are especially useful in this regard. An exemplary material useful in the compositions of the invention is "Dow Corning 344 Fluid," available from Dow Corning of Midland, Michigan. This material consists of about 77% by weight octamethylcyclotetrasiloxane and about 22% by weight decamethylpentasiloxane.

[0038] In another embodiment, the invention relates to hair conditioning compositions comprising a mixture of at least two cationically charged quaternary ammonium compounds. The first of these quaternary ammonium compounds is of formula I as described hereinabove. The second quaternary ammonium compound has the structure:



VI

10 wherein

R_6 is an alkyl or alkenyl group having from about 12 to about 36 carbon atoms,

R_7 is an alkyl or alkenyl group having from about 1 to about 36 carbon atoms or a benzyl group,

R_8 and R_9 are each independently an alkyl group having from about 1 to about 4 carbon atoms or a benzyl group,

A_2 is chloride; bromide; alkylsulfate containing from about one to about two carbon atoms; or mixtures thereof.

[0039] As was the case with the R group in the compound of formula I, R_6 and R_7 may represent groups with a single chain length or a material containing a mixture of different chain lengths.

[0040] The second quaternary ammonium compound may contain one or two fatty chains, but materials containing one fatty alkyl chain are preferred.

[0041] In a preferred embodiment, the substituents about the nitrogen atom of the second quaternary ammonium compound are as follows:

R_6 is an alkyl or alkenyl group having from about 18 to about 22 carbon atoms, preferably from about 20 to about 22 carbon atoms, and more preferably about 22 carbon atoms, and

R_7 , R_8 and R_9 are each independently an alkyl group having from about 1 to about 4 carbon atoms or a benzyl group, and more preferably a methyl group.

[0042] Exemplary materials useful as the second quaternary ammonium compound in the compositions of the invention include, but are not limited to behenalkonium chloride, available from Hoechst Celanese Company of Charlotte, North Carolina under the tradename of "Genamin KDB", dibehenylidmonium chloride, available from Witco Corp. of Dublin Ohio as "Kernamine Q-2802C," dibehenylidmonium methosulfate available from Croda, Inc. of Parsippany, New Jersey under the tradename "Incroquat DBM-90," dibehenyl/diarachidyl dimonium chloride available from Witco as "Kernamine Q-1902C," behentrimonium chloride available from Hoechst Celanese as "Genamin KDM," behentrimonium methosulfate available from Croda, Inc. under the tradename "Incroquat Behenyl TMS," and mixtures thereof. The latter material is a mixture containing 25% behentrimonium methosulfate and 75% cetearyl alcohol, and is an especially preferred raw material for the second quaternary ammonium compound in the compositions of the invention.

[0043] When both of the above-described two quaternary ammonium compounds, i.e., the compounds of formula I and formula VI, are present in the compositions of the invention, they together comprise, based upon the total weight of the composition, between about 0.01 percent to about 2.0 percent, preferably between about 0.05 percent to about 1.0 percent, and more preferably between about 0.1 percent to about 0.5 percent of the composition. The weight ratio of the first quaternary ammonium compound to the second quaternary ammonium compound is preferably in the range of about 4:1 to about 1:4, and is most preferably in the range of about 2:1 to about 1:2.

[0044] The compositions of the invention may further comprise additional components such as glycols or polyols, surfactants, and fatty alcohols. Exemplary glycols include, but are not limited to propylene glycol, butylene glycol, hexylene glycol, and mixtures thereof. An exemplary polyol useful in the compositions is glycerine.

[0045] The compositions of the invention may be in the form of a conditioning shampoo, a rinse-off conditioner, a leave-on conditioner or a hair detangler. The compositions are preferably in the form of a leave-on conditioner.

[0046] When in the form of a shampoo, the compositions of the invention typically contain surfactants at a concentration required to clean the hair, totaling in the range of about 5 percent to about 20 percent by weight of the composition. The surfactants in shampoo compositions may include anionic, nonionic or amphoteric surfactants, or mixtures of these surfactants. When in the form of a leave-on conditioner, the compositions of the invention preferably comprise a relatively smaller amount of a non-ionic surfactant typically in the range of about 0.01 percent to about 1.0 percent by weight of the composition. Exemplary classes of nonionic surfactants useful in leave-on conditioners comprising the compositions of the invention include, but are not limited to the alkoxyated alcohols and alkoxyated polyol esters. Preferably, the nonionic surfactants are ethoxyated alcohols, ethoxyated polyol esters, or mixtures thereof. Exemplary materials useful in this regard include ethoxyated lanolin and ethoxyated sorbitan esters. An exemplary ethoxyated lanolin useful in the compositions of the invention is PEG-60 lanolin; available as "Solan 50" from Croda, Inc. An

exemplary ethoxylated sorbitan ester useful in the compositions of the invention is polyoxyethylene (20) sorbitan mon-
 olaurate, available as "Tween 20" from ICI Surfactants of Wilmington, Delaware.

[0047] When in the form of a leave-on conditioner, the compositions may also comprise, based upon the total weight
 of the composition, from about 0.01 percent to about 1.0 percent of a fatty alcohol having from about 12 to about 36
 carbon atoms. Exemplary fatty alcohols include, but are not limited to lauryl alcohol, cetyl alcohol, stearyl alcohol,
 behenyl alcohol, and mixtures thereof.

[0048] When in the form of a product other than a shampoo, i.e. a leave-on conditioner or detangler, the composition
 preferably is substantially free of any anionic surfactants. By "substantially free," it is meant that the composition con-
 tains no more than 0.5 weight %, and preferably no more than 0.1 weight % of anionic surfactants.

[0049] The compositions may further comprise optional functional ingredients such as buffering agents, preservatives
 and fragrances.

[0050] For maximum convenience to the consumer, the package which contains the composition of the invention is
 preferably a dispensing package such as a spray dispenser or a foam dispenser. When the composition of the invention
 is in the form of a leave-on conditioner or a hair detangler, it is preferably contained in a spray dispenser package.
 Such packages contain a piston pump by which the composition is dispensed in the form of a mist, droplets or a stream
 of liquid. As such, leave-on conditioners or hair detanglers comprising the compositions of the invention should have
 relatively low viscosity to permit the compositions to be readily dispensed via such pump dispensers.

[0051] The compositions of the invention are especially useful in hair detangler products, where they facilitate the
 detangling of tangled hair by reducing the force required to comb tangled hair as discussed hereinabove. The compo-
 sitions may be used either when the hair is wet or dry. If the hair is wet, it is preferable that excess water be squeezed
 from the hair, and that the compositions of the invention be uniformly applied to the hair, as for example, from a spray
 dispenser. The composition may then be worked into the hair and the hair may then be combed or brushed. Alternatively,
 for use on dry hair, the compositions should be applied to the hair until the hair becomes damp and then the hair is
 combed or brushed.

[0052] Several examples are set forth below to further illustrate the nature of the invention and the manner of carrying
 it out. However, the invention should not be considered as being limited to the details thereof.

Example 1

[0053] A hair detangler composition having formula shown in Table 1 was prepared as follows:

Table 1 -

Formula of Example 1				
Ingredient	Ingredient Amount (%)	Component Chemical or CTFA Name	Component Active (%)	Net Concentration in Formulation (%)
Incroquat Behenyl TMS (Croda)	0.7	behentrimonium methosulfate	25	0.175
		cetearyl alcohol	75	0.525
Incroquat Behenyl HE (Croda)	0.3	behenamidopropyl hydroxyethyl dimonium chloride	50	0.15
		hexylene glycol	50	0.15
Dow Corning 344 Fluid (Dow Corning)	0.5	octamethylcyclo-tetrasiloxane	77	0.385
		decamethylcyclo-pentasiloxane	22	0.110
Kathon CG (Rohm & Haas)	0.025	methylchloroiso-thiazoline	1.25	0.0003
Solan 50 (Croda)	0.4	PEG-60 Lanolin	50	0.20
Fragrance	0.05		100	0.05
water	q.s. to 100			

[0054] The required quantities of Incroquat TMS, Incroquat HE, Solan 50 and DC344 Fluid were charged to a heated mixing vessel equipped with a highspeed agitator/impeller. The vessel was heated to a temperature of about 75° to 80°C to melt the ingredients, and the contents were then mixed at high speed for about 5 minutes. The water was heated in a separate vessel to about the same temperature, i.e., 75° to 80°C, then about 10% to about 15% of the total water charge was added slowly with agitation to the premelted components in the mixing vessel while the vessel was maintained at 75° to 80°C. Mixing and heating were continued for about another 10 to 15 minutes until the premelted components were totally dispersed in the water phase. The rest of the heated water was added to the mixing vessel and agitation was continued for another 10 minutes. The contents of the mixing vessel were allowed to cool to about 45°C, then the Kathon preservative and fragrance were added. The contents were allowed to further cool to room temperature.

[0055] The composition preferably has a pH of about 4 to about 5, and more preferably, between about 4.2 to about 4.4. If necessary, the pH of the composition may be adjusted with an acid such as citric acid to bring the pH of the composition to the desired value.

Example 2

[0056] A hair detangler composition having the formula shown in Table 2 was prepared following the procedure of Example 1 except that the Solan 50 was replaced by Tween 20.

Table 2 -

Formula of Example 2				
Ingredient	Ingredient Amount (%)	Component CTFA Name	Component Active (%)	Net Concentration in Formulation (%)
Incroquat Behenyl TMS	0.7	behentrimonium methosulfate	25	0.175
		cetearyl alcohol	75	0.525
Incroquat Behenyl HE	0.3	behenamido-propylhydroxyethyl dimonium chloride	50	0.15
		hexylene glycol	50	0.15
Dow Corning 344 Fluid	0.5	octamethylcyclo-tetrasiloxane	77	0.385
		decamethylcyclopentasiloxane	22	0.110
Kathon CG	0.025	methylchloroisothiazoline	1.25	0.0003
Tween 20 (ICI)	0.25	polyoxyethylene (20) sorbitan monolaurate	100	0.25
Fragrance	0.05		100	0.05
water	q.s. to 100			

Product Stability

[0057] The stability of the compositions of Examples 1 and 2 were assessed by incubating samples of the formulations at several temperatures between about ambient temperature to about 50°C and periodically measuring the pH and optical appearance of the samples. The samples, which were opaque uniform dispersions, were unchanged in appearance on aging for up to 6 weeks at temperatures from room temperature to 50°C. The pH of the samples was likewise stable over this time period. Likewise the samples were subjected to freeze-thaw stability. Each freeze-thaw cycle comprised cooling the samples to -20° to -10°C, maintaining them at this temperature for about 24 to 36 hours, and returning them to and maintaining them at ambient temperature for an additional 24 to 36 hours. There was no perceptible change in the appearance of the samples on subjecting them to 5 such freeze-thaw cycles.

Detangling Performance

[0058] The products of Example 1 and 2 were evaluated for detangling performance on consumer test panelists. Each panelist evaluated the composition of one of the examples against a commercially available control product, "Johnson's Kids No More Tangles" spray on detangler marketed by Johnson & Johnson Consumer Products, Inc. The compositions of each example were evaluated by 70 panelists in sequential (blind) nomadic tests. Each panelist was given a spray dispenser package containing the first product (either one of the compositions of Examples 1 or 2 or the control) and they were instructed to apply the product to wet hair after washing. Some of the panelists were also instructed to use the product on dry hair. After one week, the panelists were instructed not to use any detangler for three days. They were then given the second sample and instructed to apply it for a second week. Panelists were instructed to complete a questionnaire after each use. The following results were determined from the test:

Table 3 -

Detangling Performance			
	Product of Example 1	Control	Statistical Significance
Overall Liking of the product (1 =dislike extremely, 9= like extremely)	7.21	6.84	>80%
Overall detangling ability (1 =poor, 5=excellent)	3.67	3.54	<80%

Table 4 -

Detangling Performance			
	Product of Example 2	Control	Statistical Significance
Overall Liking of the product (1 =dislike extremely, 9= like extremely)	7.19	6.7	>80%
Overall detangling ability (1 =poor, 5=excellent)	3.86	3.49	>95%

[0059] The compositions were found by the panelists to improve the manageability of the hair when applied under dry or wet conditions.

[0060] Detangling efficacy was also measured on the compositions of the invention in the laboratory as follows:

[0061] Detangling was measured on one inch-wide by six inch-long tresses composed of double bleached blond hair purchased from International Hair Importers and Products, Inc. of New York City. The tresses were washed by applying 1 mL of "Tergitol 15-S-9" surfactant (Union Carbide Corp.) to the tresses, lathering for two minutes and rinsing for an additional 3 minutes. This washing procedure was repeated a total of three times. The tress was combed out to completely remove tangles. Tangles were reintroduced into the tresses by dunking the tresses in a beaker of water and removing the tresses a total of three times. The tress was clamped in a Dia-Stron 160 Series Miniature Tensile Tester (Dia-stron Ltd., Broomal, PA). A plastic comb containing teeth spaced 1/8-inch apart was also clamped to the apparatus. The Tensile Tester measures the load (in grams of force) required to pass the comb through the tress as a function of distance. The apparatus was activated and the comb force vs. distance was recorded. The tress was retangled by dunking in water and the detangling force was measured a total of three times. The average value of the peak force of three consistent readings represents the baseline value to detangle the tress. The tress was once again retangled and the efficacy of a detangler composition was determined by spraying 0.3 gm of the composition on the tress, clamping the tress in the Tensile Tester and once again measuring the peak force. The treated tress was once again retangled, and the force to run the comb through the tress was remeasured. An average of three such determinations is taken as the force to detangle the treated tress. The percent comb force reduction was computed as follows:

$$\% \text{ comb force reduction} = \frac{\text{baseline force} - \text{treated force}}{\text{baseline force}} \times 100$$

[0062] A graph showing the comb force for a tress evaluating the efficacy of the composition of Example 2 is shown in Figure 1, which plots the grams of force on the Y axis vs. distance on the X axis. The percent comb force reduction for the compositions of Examples 1 and 2 along with several other compositions is shown in Table 5.

Table 5 -

Comb Force Reduction Data	
Composition	Comb Force Reduction (%)
Example 1	97.1
Example 2	93.1
0.7% Incroquat Behenyl TMS	93.5
0.3% Incroquat Behenyl HE	84.7
0.87% Carsoquat SDQ-25 (stearylalkonium chloride)	75.7
0.25% Adogen 442 PG 75% (dimethyl dialkyl (C ₁₄ -C ₁₈) ammonium chloride)	73.3

[0063] The data indicate the excellent detangling ability of the compositions of the invention. The data also suggest that the compositions of Examples 1 and 2 incorporating the quaternary ammonium compounds behentrimonium methosulfate and behenamidopropyl hydroxyethyl dimonium chloride having the longer C₂₂ groups are more effective at detangling hair than other compositions comprising species having shorter hydrocarbon chains, i.e., stearylalkonium chloride or dimethyl dialkyl (C₁₄-C₁₈) ammonium chloride.

Eye-Irritation

[0064] The compositions of this invention also exhibited very low irritation to the eyes and skin. Irritation has been evaluated in accordance with the Invitox Protocol Number 86, the "Trans-epithelial Permeability (TEP) Assay." In accordance with the TEP Assay, the ocular irritation potential of a product can be evaluated by determining its effect on the permeability of a cell layer, as assessed by the leakage of fluorescein through the layer. In accordance with this *in vitro* method, monolayers of Madin-Darby canine kidney (MDCK) cells are grown to confluence on microporous inserts in a 24-well plate containing medium or assay buffer in the lower wells. The irritation potential of a product is evaluated by measuring the damage to the permeability barrier in the cell monolayer following a 15 minute exposure to dilutions of the product. Barrier damage is assessed by the amount of sodium fluorescein that has leaked through to the lower well after 30 minutes, as determined by spectrophotometry. The fluorescein leakage is plotted against the concentration of test material to determine the EC₅₀ (the concentration of test material that causes 50% of maximum dye leakage, i.e., 50% damage to the permeability barrier). The test procedure is set forth in Invitox Protocol Number 86 (May 1994), the disclosure of which is hereby incorporated by reference.

[0065] Exposure of a layer of MDCK cells grown on a microporous membrane to the test sample is a model for the first event that occurs when an irritant comes in contact with the eye. *In vivo*, the outermost layers of the corneal epithelium form a selectively permeable barrier due to the presence of tight junctions between cells. On exposure to an irritant, the tight junctions separate, removing the permeability barrier. Fluid is imbibed to the underlying layers of epithelium and to the stroma, causing the collagen lamellae to separate, resulting in opacity. The TEP assay measures the effect of an irritant on the breakdown of tight junctions between cells in a layer of MDCK cells grown on a microporous insert. Damage is evaluated spectrophotometrically, by measuring the amount of marker dye (sodium fluorescein) that leaks through the cell layer and microporous membrane to the lower well. Generally, a passing score is reflected in an EC₅₀ of 2.2% or higher. The undiluted composition of Example 1 made in accordance with the present invention showed no leakage and accordingly, had a passing TEP score. This data demonstrates that the compositions of the present invention are expected to be exceptionally mild to the eyes.

Examples 3-11


[0066] The formulations of Examples 3-11 shown in Table 6 are made using the procedure of Example 1.

Table 6 -- Examples 3 - 11

Ingredient	weight percent										
	Ex. 3	Ex. 4	Ex. 5	Ex. 6	Ex. 7	Ex. 8	Ex. 9	Ex. 10	Ex. 11		
Incroquat Behenyl TMS	-		-	-	-	0.04	0.2	4	2		
Incroquat Behenyl HE	0.02	0.2	1	2	4	0.3	0.3	0.3	0.3		
Dow Corning 344 Fluid	0.01	0.05	0.5	1	2	0.5	0.5	0.5	0.5		
Tween 20	0.01	0.05			1						
water	q.s. to 100	q.s. to 100	q.s. to 100	q.s. to 100	q.s. to 100	q.s. to 100	q.s. to 100	q.s. to 100	q.s. to 100	q.s. to 100	q.s. to 100

Claims

1. A composition comprising, based on the weight of the composition:
- A. from 0.01 percent to 2.0 percent of a first quaternary ammonium compound of the formula



and

B. from 0.01 to 2.00 percent of a silicone compound wherein

R is a substituted or unsubstituted alkyl or alkenyl group having from 11 to 35 carbon atoms,

X is —O— or —N(R₅)—,

R₁ is a substituted or unsubstituted alkylene group having from 2 to 6 carbon atoms,

R₂, R₃ and R₄ are each independently an alkyl or hydroxyalkyl group having from 1 to 4 atoms;





R₅ is H or CH₃, and

A₁ is chloride; bromide; alkylsulfate containing from one to two carbon atoms; or mixtures thereof.

2. The composition of claim 1 comprising from 0.1 to 1.0 percent by weight of said first quaternary ammonium compound.


3. The composition of claim 1 or claim 2 wherein R is an alkyl group having from 19 to 21 carbon atoms or mixtures thereof, X is an —N(R₅)— group and R₅ is H.

4. The composition of any one of claims 1 to 3 wherein said quaternary ammonium compound is:



or E. a mixture thereof.

5. The composition of any one of claims 1 to 4, which further comprises a second quaternary ammonium compound of the formula:




and wherein

R_6 is an alkyl or alkenyl group having from 12 to 36 carbon atoms,
 R_7 is an alkyl or alkenyl group having from 1 to 36 carbon atoms or benzyl group,
 R_8 and R_9 are each independently an alkyl group having from 1 to 4 carbon atoms or a benzyl group,
 A_2 is chloride; bromide; alkylsulfate containing from one to two carbon atoms; or mixture thereof,

and wherein said first quaternary ammonium compound and said second quaternary ammonium compound together comprise between 0.01 percent to 2.0 percent by weight of said composition.

6. The composition of claim 5 wherein the weight ratio of said first quaternary ammonium compound to said second quaternary ammonium compounds is from 4:1 to 1:4.
7. The composition of any one of claims 1 to 6 comprising from 0.05 to 1.0 percent by weight of said silicone compound.
8. The composition of any one of claims 1 to 7 wherein said silicone compound is a volatile polydimethyl siloxane having from 4 to 6 silicon atoms.
9. The composition of any one of claims 1 to 8 which further comprises a glycol or polyol having 3 to 6 carbon atoms.
10. The composition of any one of claims 1 to 9 which further comprises from 0.01 to 1.0 percent by weight of a nonionic surfactant.
11. The composition of any one of claims 1 to 10 in the form of a conditioning shampoo, a rinse-off conditioner, a leave-on conditioner or a hair detangler.
12. A spray dispenser package or a foam dispenser package containing within it the composition of any one of claims 1 to 11.
13. A method of conditioning or detangling hair comprising applying to the hair a conditioning or detangling-effective amount of the composition of any one of claims 1 to 11.

FIG. 1





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 99 30 0932

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
X	WO 93 07848 A (HELENE CURTIS) 29 April 1993 (1993-04-29) * claims 1,3-5,9 * * page 17, line 2-17 * * page 35, line 13-35 * * page 39, line 9-11 *	1-8,10, 11,13	A61K7/06 A61K7/50
X	EP 0 566 049 A (HELENE CURTIS) 20 October 1993 (1993-10-20) * claims 1-3,5-7 * * page 16, line 19-57 * * page 19, line 20-32 *	1-6, 8-11,13	
D,X	US 5 288 484 A (A. TASHJIAN) 22 February 1994 (1994-02-22) * claims 1,8 * * column 4, line 4 - column 5, line 2 * * column 5, line 52-68 * * column 6, line 20-37 *	1-4,9, 11,13	
			TECHNICAL FIELDS SEARCHED (Int.Cl.6)
			A61K
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 21 July 1999	Examiner Peeters, J
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03.92 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 99 30 0932

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

21-07-1999

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9307848 A	29-04-1993	US 5277899 A	11-01-1994
		AU 2783892 A	21-05-1993
		CA 2117264 A	29-04-1993
		EP 0663813 A	26-07-1995
		JP 7500334 T	12-01-1995
EP 566049 A	20-10-1993	US 5275761 A	04-01-1994
		AT 140614 T	15-08-1996
		AU 3550393 A	21-10-1993
		CA 2092284 A	16-10-1993
		DE 69303752 D	29-08-1996
		DE 69303752 T	20-02-1997
		DK 566049 T	09-12-1996
		ES 2090756 T	16-10-1996
		FI 931675 A	16-10-1993
		GR 3021383 T	31-01-1997
		IL 105250 A	10-06-1997
		JP 2559973 B	04-12-1996
		JP 6080539 A	22-03-1994
		MX 9302157 A	29-04-1994
		NZ 247370 A	27-06-1995
		US 5358667 A	25-10-1994
		US 5456863 A	10-10-1995
		ZA 9301613 A	15-11-1993
US 5288484 A	22-02-1994	NONE	

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82